

COURTESY

Direct Dial Handset Phones



Model Numbers: 2300-710_ (Coil Cord - in white, red or black)
2300-746_ (Armor Cord)

Size: 9" H x 5 1/2" W x 5" D

Style: Interior handset desk phone

Feature: Auto dials pre-programmed number when receiver is lifted

Option(s): Custom artwork/wording
Standard or custom colors
2 button/ 2 number



Model Numbers: 2300-610_ (Coil Cord - in white, red or black)
2300-646_ (Armor Cord)

Size: 8 1/2" H x 4" W x 4 1/2" D

Style: Interior handset wall phone

Feature: Auto dials pre-programmed number when receiver is lifted

Option(s): Custom artwork/wording
Standard or custom colors
2 button/ 2 number



Model Number: 2300-841 (Single Button)
2300-842 (Dual Button)

Size: 16" H x 11" W x 4" D

Style: Wall or surface mount module

Feature: Auto dials pre-programmed number when receiver is lifted and button is pressed

Option(s): Handset color and logo wording

Paratransit



Taxis/Limos



Flight for Life



Car Rental



Model Numbers: Wall: 2300-630_ (Coil Cord - in white, red or black)
Desk: 2300-730_ (Coil Cord - in white, red or black)
Wall: 2300-636_ (Armor Cord)
Desk: 2300-736_ (Armor Cord)

Size: 8 1/2" H x 4" W x 4 1/2" D (Wall Phone)
9" H x 5 1/2" W x 5" D (Desk Phone)

Style: Interior handset wall/desk phone with keypad

Feature: Auto dials pre-programmed number when receiver is lifted

Option(s): Standard or custom colors

Model Number: 2300-674RD

Size: 10" H x 4" W x 4" D

Style: Interior handset phone

Feature: Auto dials pre-programmed number when receiver is lifted

Option(s): Handset color and wording



COURTESY

Direct Dial Handset Phones

► Rath Microtech General Features:

- Telephone line powered
- 2 year warranty
- Volume control handset
- Meets ADA requirements for handset courtesy phones
- On-site programming
- Automatic dialer (31 digit programmable memory)
- Non-volatile EEPROM memory
- Optional 2-button/ 2-number capability
- Optional keypad: Active only after automatic dialing is complete and used to dial extensions or input data in automated systems
- Optional ringer available upon request, needed if customer will be calling back into phone
- Custom artwork available
- Available in 8 standard colors (see below) or custom PMS colors available at an additional charge
- Temperature range -40°F to +150°F
- Maximum of 3 phones on one phone line
- Touch Tone operation only (Touch Tone is an AT&T registered trademark)
- Requires analog telephone line either POTS, PBX or central office phone line. If used on a digital system must order an ATA analog telephone adaptor from digital system provider. Make sure they program it with a standard wink signal.
- Compatible with VOIP networks when using an (ATA) analog telephone adaptor
- On hook telephone line voltage: 24V-48V
(Off hook: 48V=6.43V and 24V=6.36V)
(Most standard telephone lines are 48V & many switchboard/PBX lines are 24V)
- Loop current: (48V=23.78mA and 24V=24mA)
- Ringer equivalent number (REN): 1.2B
- FCC Part 68 Registered

