

PUBLIC SAFETY

Emergency Speaker Phones

► Rath Microtech Emergency Phone Features:

- Telephone line powered
- 2 year warranty
- On-site programming
- Automatic dialer (31 digit programmable memory)
- Non-volatile EEPROM memory
- Optional 2-button/ 2-number capability
- Temperature range -40°F to +150°F
- Touch Tone operation only (Touch Tone is an AT&T registered trademark)
- Analog telephone line required (works on both PBX & central office phone lines)
- Compatible with VOIP networks when using an (ATA) Analog Telephone Adaptor
- Maximum of 3 phones on one phone line
- Automatic answer feature
- Audible ring
- On hook telephone line voltage: 24V-48V (off hook: 48V=8.27V and 24V=8.25V)
(most standard telephone lines are 48V & many switchboard/PBX lines are 24V)
- Loop current: (48V=23.76mA and 24V=23.83mA)
- Ringer equivalent number (REN): 1.0B
- LED: 2vdc, 1/3 watt
- FCC Part 68 Registered

RATH MICROTECH

Emergency Communication Solutions

N56 W24720 N. Corporate Circle • PO Box 306 • Sussex, WI 53089

800-451-1460 • 262-246-4828 (fax) • www.rathmicrotech.com • E-mail: jcpierce@bmgmail.com

Buildings • Grounds • Pool Areas • Parking Lots • Elevators

Model Number Style Size Standard Color(s) Options



2400-910RD

Interior speaker phone

8 1/8" H x
5 1/8" W x 2 1/8" D

Red

Gray box
Custom wording



2400-974RD

Interior/exterior enclosure with door speaker phone

13 9/16" H x
11 7/16" W x 5 1/4" D

Red

Gray box
Custom wording



2400-984RD

Interior/exterior enclosure speaker phone

9 1/2" H x
6" W x 2 7/8" D

Red

Gray box
Custom wording



2400-976RD

Interior/exterior enclosure with door dual purpose 2 button with keypad speaker phone

13 9/16" H x
11 7/16" W x 5 1/4" D

Red

Gray box
Custom wording



2400-948SSK

Interior dual purpose 2 button with keypad speaker phone

Plate:
12 1/2" H x 9 3/4" W
Back Box:
8" H x 6" W x 3" D

Brushed Stainless Steel

Custom wording

Buildings • Grounds • Pool Areas • Parking Lots • Elevators